

A211A

# CYLINDER HEAD PRESSURE TESTER MACHINE

# *SHC 120*

**PRESSURE TESTER FOR THE DETECTION  
OF CRACKS IN CYLINDER HEADS  
COOLING CIRCUITS**

**MINIMUM MAINTENANCE  
AUTOMATIC PROGRAMMER FOR HEATING START / STOP TIME  
ELECTRONIC TEMPERATURE REGULATOR WITH DIAL DISPLAY  
EASY CLAMPING DEVICE WITH 360° TURNING SYSTEM  
EASY EMPTYING AND CLEANING OF THE DRUM  
THERMOINSULATED STAINLESS STEEL CASK FOR LOW CONSUMPTION**



# Honingtec

## TECHNICAL FEATURES

		SHC 120
Maximum stroke	mm	600
Rotation speed	r.p.m.	4
Heating power	kw	2 x 4,5
Stroke hydraulic power	kw	0,37
Turning power	kw	0,18
Voltage		220 / 380 V 3 PH + N + E
Frequency	Hz	50 - 60
Manoeuvre voltage		24 V A C
Total power	kw	14
Machine dimensions	mm	Length: 1960 Width: 960 Height: 1670 / 1070
Machine net weight	kg	400
Maximum unit capacity (with 360° rotation)	mm	Length: 1200 (1227) Width: 338 Height (over plane supports): 205
Maximum weight piece	kg	125
Water capacity	l	420
Time to heat from ambient temperature	min	120
Package dimensions	mm	2210 x 1200 x 1360

## STANDARD ACCESSORIES

- 6 u. Ref 1300-101-15 Male quick connection
- 1 set (2 u.) Ref 1300-560 Plane supports.
- 1 set (2 u.) Ref 1300-300 Supports for inclined heads.
- 1 set (4 u.) Ref 1300-281 Uper plane supports.
- 8 Long-threaded bars with accessories.
- 8 Short-threaded bars.
- 2 Transparent plates:                   Ref 1300-63   800 x 220 x 30 mm  
  Ref 1300-64   800 x 330 x 30 mm
- 1 Set Ref 1300-49-56 rubber plugs ( 90 units ).
- 1 u. Ref 1300-49-70 Rubber plate to manufacture special plugs ( 200 x 290 x 4 mm )
- 1 Bottle Ref AGUA NOCAL Rust protective and softener for the water
- 1 Service operation and maintenance manual.

**NOTE :** We reserve the right to change specifications without prior warning.



### **HONINGTEC, S.A.**

C/ Sant Jaume, 8-14  
08550 HOSTALETS DE BALENYÀ  
Barcelona (España)  
Tel. 34-93 889 84 10 / 34-93 889 80 44  
Fax 34-93 889 82 76  
E-mail: honingtec@honingtec.com  
<http://www.honingtec.com>

DISTRIBUTOR