

A212

CYLINDER HEAD PRESSURE TESTER MACHINE

SHC 150

**PRESSURE TESTER FOR THE DETECTION
OF CRACKS IN CYLINDER HEADS
COOLING CIRCUITS**

MINIMUM MAINTENANCE

AUTOMATIC PROGRAMMER FOR HEATING START / STOP TIME

ELECTRONIC TEMPERATURE REGULATOR WITH DIAL DISPLAY

EASY CLAMPING DEVICE WITH 360° TURNING SYSTEM

EASY EMPTYING AND CLEANING OF THE DRUM

THERMOINSULATED STAINLESS STEEL CASK FOR LOW CONSUMPTION



Honingtec

TECHNICAL FEATURES

		SHC 150
Maximum stroke	mm	650
Rotation speed	r.p.m.	4
Heating power	kw	4 x 4,5
Stroke hydraulic power	kw	1,1
Turning power	kw	0,37
Voltage		220 / 380 V 3 PH + N + E
Frequency	Hz	50 - 60
Manoeuvre voltage		24 V A C
Total power	kw	22
Machine dimensions	mm	Length: 2280 Width: 1080 Height: 1240 / 1890
Machine net weight	kg	500
Maximum unit capacity (with 360° rotation)	mm	Length: 1500 (1527) Width: 388 Height (over plane supports): 300
Maximum weight piece	kg	250
Water capacity	l	700
Time to heat from ambient temperature	min	120
Package dimensions	mm	2310 x 1350 x 1460

STANDARD ACCESSORIES

- 6 u. Ref 1300-101-15 Male quick connection
- 3 u. Ref 1404-56 Down plane supports.
- 4 u. Ref 1404-28 Upper plane supports
- 2 u. Ref 1404-31 Supports for inclined heads.
- 8 u. Long-threaded bars with accessories.
- 8 u. Short-threaded bars.

- 2 Transparent plates: Ref 900212 1400 x 330 x 30 mm
- Ref 1300-64 800 x 330 x 30 mm

- 1 u. Ref 1300-49-55 Set of rubber plugs (50 units).
- 1 u. Ref 1300-49-71 Rubber plate to manufacture special plugs (700 x 500 x10 mm)
- 1 u. Ref AGUA NOCAL Rust protective and softener for the water
- 1 Service operation and maintenance manual.

NOTE : We reserve the right to change specifications without prior warning.



HONINGTEC, S.A.

C/ Sant Jaume, 8-14
 08550 HOSTALETS DE BALENYÀ
 Barcelona (España)
 Tel. 34-93 889 84 10 / 34-93 889 80 44
 Fax 34-93 889 82 76
 E-mail: honingtec@honingtec.com
<http://www.honingtec.com>

DISTRIBUTOR